

(12) 按照专利合作条约所公布的国际申请

(19) 世界知识产权组织  
国际局



(43) 国际公布日:  
2004年6月3日(03.06.2004)


PCT

(10) 国际公布号:  
WO 2004/046576 A1

- (51) 国际分类号<sup>7</sup>: F16D 59/00, 67/00
- (21) 国际申请号: PCT/CN2003/000945
- (22) 国际申请日: 2003年11月10日(10.11.2003)
- (25) 申请语言: 中文
- (26) 公布语言: 中文
- (30) 优先权:  
02150200.5 2002年11月16日(16.11.2002) CN
- (71)(72) 发明人/申请人: 谢兴云(XIE, Xingyun) [CN/CN];  
中国湖南省长沙市河西桐梓坡72栋西头一楼, Hunan  
410013 (CN).
- (74) 代理人: 湖南兆弘专利事务所(HUNAN ZHAOHONG  
PATENT LAW OFFICE); 中国湖南省长沙市芙蓉中  
路185号顺天城2701室赵洪, Hunan 410011 (CN)
- (81) 指定国(国家): AE, AG, AL, AM, AT, AU, AZ, BA,  
BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ,  
DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE,  
GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP,  
KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY,  
TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN,  
YU, ZA, ZM, ZW
- (84) 指定国(地区): ARIPO专利(GH, GM, KE, LS, MW,  
MZ, SD, SL, SZ, TZ, UG, ZM, ZW), 欧亚专利(AM,  
AZ, BY, KG, KZ, MD, RU, TJ, TM), 欧洲专利(AT,  
BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB,  
GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK,  
TR), OAPI专利(BF, BJ, CF, CG, CI, CM, GA, GN,  
GQ, GW, ML, MR, NE, SN, TD, TG)
- 本国际公布:  
— 包括国际检索报告。
- 所引用双字母代码和其它缩写符号, 请参考刊登在每期  
PCT公报期刊起始的“代码及缩写符号简要说明”。

(54) Title: A SHAFT COUPLING UNIT

(54) 发明名称: 轴用活套装置



(57) Abstract: A shaft coupling unit is disclosed, which comprises a coupling disk (1), a disk (2), a spring (3), a concave member (4), a convex member (5) and a draw lever (14). The concave member (4) is press fitted against the convex member (5) to rotate circumferentially and to move axially with respect to one another. The concave member (4) is axially press fitted against the disk (2) to rotate circumferentially with respect to one another. An external coupling member (6) is disposed between the concave member (4) and a transmission member (7). The external coupling member (6) is radially press fitted against the concave member (4) to axially slide each other. The convex member (5) is mounted on the coupling disk (1). The spring (3) is joined to the disk (2) at an end, and joined to the draw lever (14) at the other end. The draw lever (14) is linked up with the coupling member (1) through the disk (2). The coupling disk (1) is mounted on an external transmission shaft (8), or attached to the latter through a shaft joining member (9) so as to form the shaft coupling unit of the invention for coupling the transmission member (7) with the external transmission shaft (8).

[见续页]